

theMova S360-100 AP BK

Item no.: 1030552



Presence and motion detectors
Ceiling installation indoor

Description

- Passive infra-red motion detector for ceiling installation
- Circular detection area 360°, up to Ø 9 m (64 m²)
- Automatic motion and brightness-dependent control for lighting
- Mixed light measurement
- Channel A light: relay, 230 V
- Operation as fully automatic device
- Brightness switching value configurable, teach-in function
- Pulse function for staircase light time switch
- Time delay configurable
- Detection sensitivity configurable
- Test mode for checking function and detection area
- Ready for immediate use due to factory presetting (Brightness switching value 300 lux, Time delay 10 min.)
- One of these optional remote controls is required for changing the values and attitudes:
- Management remote control SendoPro
- Installation remote control theSenda P
- Optional user remote control: theSenda S



Technical data

theMova S360-100 AP BK	
Operating voltage	230 V AC
Frequency	50 Hz

theMova S360-100 AP BK	
Installation height	2 - 4 m
Installation type	Ceiling installation, Surface mounted

theMova S360-100 AP BK

Item no.: 1030552




Technical data

theMova S360-100 AP BK	
Colour	Black
Switching output	Light
Power consumption	~0.5 W
Light measurement	Mixed light measurement
Setting range brightness	30 - 3000 lx
Light switch-off delay	10 s - 60 min
Type of contact light	Relay 230 V/10 A µ-contact
Lamp types	Incandescent/halogen lamps, fluorescent lamps, Energy saving lamps, LEDs
Incandescent/halogen lamp load	2300 W
Compact and flourescent lamps	1150 VA (cos φ = 0,5)

theMova S360-100 AP BK	
Inrush current	max. 400 A / 200 µs
LED lamp < 2 W	25 W
LED lamp 2-8 W	250 W
LED lamp > 8 W	250 W
Type of connection	Spring terminals
Detection range	50 m² (ø 8 m)
Detection angle	360°
Ambient temperature	-15°C ... 50°C
Type of protection	IP 54 (when fitted)
GWP Cradle-to-Gate (A1-A3)	4.77 kg CO ₂ eq
GWP Cradle-to-Grave (A1-C4)	21.27 kg CO ₂ eq

Connection example



Detection range for planning applications at a temperature of 21 °C


Mounting height (A)	Head on to (R)	Diagonally (t)
2 m	5 m² 2.5 m	38 m² 7 m
2.5 m	7 m² 3 m	38 m² 7 m
3 m	13 m² 4 m	50 m² 8 m
3.5 m	13 m² 4 m	50 m² 8 m
4 m	13 m² 4 m	64 m² 9 m

theMova S360-100 AP BK


Item no.: 1030552

theben

Detection range for planning applications at a temperature of 21 °C



Scale drawings



Subject to technical changes and misprints

additional information at: www.theben.de/product/1030552

The load data are determined with exemplary selected illuminants and are therefore typical data due to the large number of available products.

30/07/2026

Page 3 of 4

theMova S360-100 AP BK

Item no.: 1030552

theben

Accessories

theSenda P

Item no.: 9070910



theSenda S

Item no.: 9070911




theSenda B

Item no.: 9070985



QuickSafe

Item no.: 9070531



Subject to technical changes and misprints

additional information at: www.theben.de/product/1030552

The load data are determined with exemplary selected illuminants and are therefore typical data due to the large number of available products.

30/07/2026

Page 4 of 4