
TA 4.1 KNX

Item no.: 4969274

KNX
KNX Secure

Description

- 4-way binary input push-button interface KNX TP
- 2 NTC inputs for detection of the actual temperature from -5 °C to +100 °C
- Secure commissioning and communication through support of KNX Data Secure
- Identification of the wire pairs via color coding
- Connectable cable length up to 30 m
- Can be installed in flush-mounted sockets with conventional sensors / switches
- Flexible LED controlling, thanks to increased output current of 3 mA commercially available LEDs and low curent LEDs can be controlled
- Inputs can be reconfigured to outputs with parameterizable flashing and pulsing function
- Colour coding of wiring pairs





Technical data

	TA 4.1 KNX
Operating voltage KNX	Busspannung, ≤10 mA
Installation type	in flush-mounted socket
Type of connection	KNX bus terminal
Number of inputs	4
Max. cable length	30 m
Length connecting wires	25 cm

	TA 4.1 KNX
Contact current	0.5 mA
Reaction in case of bus recovery	Adjustable
Ambient temperature	-5°C ... 45°C
Type of protection	IP 20
Protection class	III

Scale Drawings





Accessories

Temperature sensor
Item no.: 9070321



Flush-mounted temperature sensor
Item no.: 9070496



Temperature sensor RAMSES IP 65
Item no.: 9070459

