

TR 611 top3 RC

Item no.: 6110330

theben

Time and light control Digital time switches

Description

- Digital time switch with weekly program
- Time synchronisation option via connection of an external DCF or GNSS antenna
- 1 channel
- Programming by app possible
- Safe transfer via optional Bluetooth Low Energy OBELISK top3
- Maximum manipulation security, time switch programs can only be transferred from the app to the time switch when the Bluetooth OBELISK top3 is plugged into the time switch
- 100% compatible with top2 (When transferring the switching programs via OBELISK to the PC, the OBELISK software as of V3.8.3.4 must be installed)
- 3 special programs (small annual program)
- External inputs
- Connectable sensors (external selector switch, sequence timer)
- Connectable switches (ON or OFF permanent switching)
- ReShape: Plastic housing (upper and lower housing sections, slider) containing 93% recycled material from industrial waste (PIR - Post Industrial Recycled)
- DuoFix spring terminals
- For 2 conductors each
- Wire or strand (with or without wire end sleeve)
- Wire diameter: 0.5 - 2.5 mm²
- Button for releasing plug-in connection
- Text-oriented user guidance in display
- Preset date and time
- fully operable without mains connection
- 84 memory locations
- Interface for OBELISK top2 memory card (PC programming)
- 2. insertable switching program
- Copying programs
- Storing programs
- 10 year power reserve (lithium battery)
- Zero-cross switching for relay-saving switching and high lamp loads (not with 24 V devices)
- ON-OFF switching times
- Pulse program
- Cycle program
- Switching preselection
- Permanent switching ON/OFF
- Timer countdown
- Integrated operating hour counter
- Reset option



Subject to technical changes and misprints

additional information at: www.theben.de/product/6110330

The load data are determined with exemplary selected illuminants and are therefore typical data due to the large number of available products.

TR 611 top3 RC

Item no.: 6110330

Description


- Service function for monitoring maintenance intervals
- Holiday program
- 2 random programs
- Display back light (can be turned off)
- Permanent switching ON/OFF
- PIN coding
- Automatic summer/winter time changeover
- can be deactivated
- Date rule options are already stored for Europe, the USA and other countries
- own date rule options or changeover around set dates are available

Technical data

| TR 611 top3 RC | |
|--|--|
| Operating voltage | 110 - 230 V AC |
| Frequency | 50 - 60 Hz |
| Width | 2 modules |
| Installation type | DIN rail |
| Type of contact | Changeover contact |
| Switching output | Phase-independent |
| Opening width | < 3 mm |
| Program | Weekly program, kleines Jahresprogramm |
| Program functions | ON-OFF, Pulse, Cycle |
| Number of channels | 1 |
| External inputs | 1 |
| Number of memory locations | 84 |
| Power reserve | 10 years |
| Switching capacity at 250 V AC, $\cos \varphi = 1$ | 16 A |
| Switching capacity at 250 V AC, $\cos \varphi = 0,6$ | 10 A |
| Incandescent/halogen lamp load | 2600 W |
| Energy saving lamps | 1100 W |

| TR 611 top3 RC | |
|---------------------------------|--|
| LED lamp < 2 W | 50 W |
| LED lamp 2-8 W | 600 W |
| LED lamp > 8 W | 600 W |
| Inrush current | max. 800 A / 200 μ s |
| Switching capacity min. | ca. 10 mA |
| Shortest switching times | 1 s |
| Time accuracy at 25 °C | typical $\pm 0,25$ s/day (quartz) or DCF77/GPS |
| Time basis | Quartz/DCF77/GNSS |
| Stand-by consumption | $\sim 0,75$ W |
| Type of connection | DuoFix spring terminals |
| Externe Antenne anschlieÙbar | √ |
| Display | LCD |
| Keyboards | 4 touch buttons |
| Housing and insulation material | High-temperature resistant, self-extinguishing thermoplastic |
| Type of protection | IP 20 |
| Protection class | II according to EN 60 730-1 |
| Ambient temperature | -25°C ... 55°C |

Connection example



Subject to technical changes and misprints

additional information at: www.theben.de/product/6110330

The load data are determined with exemplary selected illuminants and are therefore typical data due to the large number of available products.

19/05/2026

Page 2 of 3

TR 611 top3 RC

Item no.: 6110330

Scale drawings



Accessories

Wall mounting kit 35 mm
Item no.: 9070064



Antenna RC-DCF
Item no.: 9070410



PC set OBELISK top2/3
Item no.: 9070409



Memory card OBELISK top2
Item no.: 9070404



Front panel kit
Item no.: 9070001



Bluetooth OBELISK top3
Item no.: 9070130



Antenna RC-GNSS R
Item no.: 9070807



Antenna RC-GNSS
Item no.: 9070823



Subject to technical changes and misprints

additional information at: www.theben.de/product/6110330

The load data are determined with exemplary selected illuminants and are therefore typical data due to the large number of available products.