

AMUN 716 SR

Item no.: 7160110

Climate control
Sensor technology

Description

- CO₂ sensor
- Suitable for conference and meeting rooms, offices, schools/nurseries, passive and low-energy housing.
- For fan control
- Warning display for CO₂ concentration (lights)
- Power unit optionally available. Power unit is suitable for flush mounted installation
- Simple upgrade of uncontrolled ventilation systems possible
- 2 switch outputs CO₂ controlled for 2 stage control, with manual and automatic mode as well as display of switching status
- 3 x 0–10 V outputs for CO₂, temperature and relative humidity



Technical data

AMUN 716 SR	
Operating voltage	24 SELV V AC/DC
Output	3 x 0-10 V, 2 x relay 5 A/250 V AC
Measuring range CO ₂	0 - 5000 ppm
Measuring range temperature	5°C ... 40°C
Measuring range humidity	30 - 80 % rF
ON/OFF thresholds	700 ppm ±200 ppm, 1300 ppm ±200 ppm

AMUN 716 SR	
Type of connection	Screw terminals
Display	6 LEDs
Installation type	Wall installation (also on flush-mounted socket possible)
Type of protection	IP 20
Protection class	II according to EN 60 730-1

Subject to technical changes and misprints

additional information at: www.theben.de/product/7160110


The load data are determined with exemplary selected illuminants and are therefore typical data due to the large number of available products.

AMUN 716 SR

Item no.: 7160110

theben

Scale drawings



Accessories

Power unit CO2-sensor

Item no.: 9070494



Subject to technical changes and misprints

additional information at: www.theben.de/product/7160110

The load data are determined with exemplary selected illuminants and are therefore typical data due to the large number of available products.